

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 7 only, T31-2E

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Peter Applegate, US Deputy Surveyor under contract #571 dated April 10, 1891 - (DCSO records Vol. 26 Page(s) 11164)

-----  
Set a stone 15x10x6", 10" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which  
A W.Fir, 20" dia., bears N.80°E., 11 lks., mkd: ¼ S BT.  
A cedar, 10" dia., bears N.66°W., 7 lks., mkd: ¼ S BT.

GLO dependent resurvey by Leonard Carter, Public Land Surveyor, under Group No. 175, surveyed Sept./Nov. 1936 - (DCSO Vol. 46 Page(s) 17626-7)

-----  
The old ¼ sec. cor. of secs. 7 & 12, which is a basalt stone, 15x10x6", loosely set, mkd. ¼ on W face.  
I change this cor. to refer to sec. 7 only.  
At point for cor.  
Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for ¼ sec. cor. of sec. 7 only, with brass cap mkd:

|  
¼ S 7  
1936

from which  
A W.Fir, 30" dia., bears N.73°E., 14 lks., blaze healed;  
I do not open (Old BT)  
A cedar, 12" dia., bears N.45°W., 8 lks., mkd. ¼ S BT. I obliterate the marks. (Old BT)  
A cedar, 22" dia., bears N.32°E., 81 lks., mkd. ¼ S7 BT (New BT)  
A W.Fir, 35" dia., bears S.47°E., 71 lks., mkd: ¼ S7 BT. (New BT)