

TOWNSHIP 32 RANGE 01 POINT IDENTIFIER # 140400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 18 & 19

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Rufus S. Moore, Deputy Surveyor, under contract 475 dated July 3, 1883 - (DCSO records Vol. 19 Page(s) 8278)

Set a fir post, 3 ft. long, 3" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S on N face; from which

A fir, 10" dia., bears N.45°W., 3 lks., mkd: ¼ S BT.

A fir, 8" dia., bears S.47°W., 8 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell - 7/1968 - C.S. File 54/71

Reported as not found.

Orig. cor. not fd. Area logged & burnt. Fd. 1" steel axle @ approx. cor., no BTs.

Douglas Co. Surveyors Office - M. Lenora Ladig - Karen Cheney - Pete L. Earle - 6/30/1976 - C.S. file 59/15-25

Found - An unrecorded 1" steel axle in mound of stone with 4"x4" wood post laying alongside. (First noted in C.S. 54/71)

Found no trace of BTs

The 1" steel axle is in area good for orig. GLO line notes. Area has been logged and burnt.

Note - Did not monument this corner.

Compass Dec. 20°East.

Glenn S. Baughman - For: USFS, Tiller Land Survey #20 - Dec. 1976 - M56-69

Set - 2½"x30" IP with brass cap stamped T32S R1W ¼ S18 S19 OLS 536 1976.

New - 8" Pine bears N.43°W. 28.8 ft scribed T32S R1W ¼ S18 BT

6" Fir bears S.63°E., 16.9 ft scribed T32S R1W ¼ S19 BT

Fd. OK by R. Wytcherley, May 2004 - M144-49

BLM dependent resurvey by Francis J. Simon, Cadastral Surveyor under Group #2007, surveyed April/June 2002 - (DCSO records Vol. 54 Page(s) 21251)

The ¼ sec. cor. of secs. 18 & 19, reestablished at proportionate measurement by Baughman, in 1976. There is no remaining evidence of the original cor.; therefore this point is accepted as the cor.; monumented with an iron post, 2½" dia., firmly set, projecting 10" above the ground, in a collar of stone, with brass cap (properly) mkd.

continued next page

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 18 & 19

Alias	Description
Alias	Description
Alias	Description
Alias	Description

from which bearing trees mkd. by Baughman
A fir, 14" dia., bears S.65°E., 17.0 ft., with a healed blaze.
A ponderosa pine, 17" dia., bears N.46¾°W., 28.9 ft. with a healed blaze.

John Ransom, USFS - Jonathan Drew - 9/2013 - C.S. 65/85-26

Found - 3" brass cap (properly mkd) on 2½" iron post projecting 3" above a 2 ft dia. mound of stone.
16" Fir S.64°30'E. 17.0 ft healed double blaze
19" high stump N.46°W. 28.7 ft fir high stump, detached healed face

New - A 2" alum cap on 5/8" rebar, projecting 7" above the ground bears, N.46°W. 24.6 ft. Cap mkd "RML PLS2561 2013"
A 7" Fir bears, N.19°45'E. 16.9 ft. Scribed "X" "BT" on a double blaze
A 14" Fir bears, S.55°W., 11.1 ft, scribed "¼ S19" "BT" on a double blaze.
New BTs include a 3/4" brass washer stamped "LS2561" nailed to lower blaze.
Red paint applied to BT faces and a 6" band at head height, BTs include BT & survey monument tags
Brush cleared around monument and to BTs
"LAND LINE" flagging tied on monument & guard posts

Note- Corner falls on south side of graveled road about 30 ft from centerline, BTs visible from road. Also falls on south timberline of a private clear cut.
Take FS road 1615 to corner
Measurements to accessories made with LEICA 1103+ Total Station with reflectorless EDM to aluminum nail set at side center, basis of bearing being plat record bearing(N.89°40'39"W.) (M56-69) After rotating open traverse between this corner and section corner to the west
Maintained line .5 miles west of corner.