

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 6 & 7

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>GLO survey by Rufus S. Moore, Deputy Surveyor, under contract 475 dated July 3, 1883 - (DCSO records Vol. 19 Page(s) 8284)</p> <p>-----</p> <p>Set a fir post, 3 ft. long, 3" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S on N face; from which A matherone, 6" dia., bears N.50°E., 10 lks., mkd: ¼ S BT. A fir, 12" dia., bears S.50°W., 10 lks., mkd: ¼ S BT.</p>
<p>Douglas Co. Surveyors Office - James W. Byron, Deputy - Mike Darby & Wm Stoffel - March 1963 - C.S. File 53/15</p> <p>-----</p> <p>Found - Orig. 12", now 16" dead Fir S.50°W., 6.6 ft. shows good scribing "¼S" Orig. NE BT not found. Set brass cap at cor. mkd: COUNTY SURVEYORS ¼ $\frac{S\ 6}{S\ 7}$ T32S R1W OFFICE 1968 New BTs- 14" W.Fir bears N.60°W., 17.2 ft scribed ¼ S6 CS BT. 22" R.Fir bears S.72°W., 12.0 ft scribed ¼ S7 CS BT.</p>
<p>Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - July 1968 - C.S. File 54/71</p> <p>-----</p> <p>Found - C.S. brass cap, set & marked in 1963 14" W.Fir, now 15" N.60°W., 17.2 ft. scribe visible. 22" R.Fir, now dead, S.72°W., 12.0 ft scribe visible New BT - 9" D.Fir S.53°E., 133.5 ft. mkd: ¼ S7 CS BT.</p>
<p>Raymond Wytcherly - For: Boise Cascade Corp. - May 2004 - M144-50</p> <p>-----</p> <p>Found - 1963 County brass cap from which A W.Fir stump bears N.60°W., 17.2 ft., face rotted. A D.Fir snag, 5 ft. high bears S.72°W., 12.0 ft. face healed over. New BTs- A fir 10" dia., bears N.1°28'W., 48.41 ft., scribed "¼ S 6 BT" A Fir 7" dia., bears N.52°E., 14.24 ft., scribed "¼ S 7 BT" A Pine 8" dia., bears S.67°W., 24.60 ft., scribed "¼ S 7 BT" A Pine 9" dia., bears S.20°E., 39.24 ft., scribed "¼ S7 BT"</p>
<p>Jonathan B. Drew, II, USFS - Assisted by: Lance Goucher - 5/12/2015 - C.S. File 65/90-19</p> <p>-----</p> <p>Found - A 2½" DCSO brass cap on 1¼" galvanized iron pipe, projecting 15" above a mound of stone. cont.</p>

TOWNSHIP 32 RANGE 01 POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 6 & 7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

No trace found of a (6" matherone)1883
No trace found of a (12" fir)1883
An indeterminate size rotten fir stump with no marks visible, rec. (N.60°W., 17.2') 1963
A 16" rotten fir high stump with no marks visible, rec. (S.72°W., 12.0')1963
A Fir root hole and shell shows healed single blaze, rec. 12" log alongside, (S.53°E., 133.5')1968
A 15" fir with a healed single blaze, rec. (N.1°28'W., 48.41')2004
A 11" Fir with a healed single blaze, rec. (N.52°E., 14.24')2004
A 13" pine with scribe visible on a partially healed single blaze, rec. (S.67°W., 24.6') 2004
A 13" pine with scribe visible on a partially healed single blaze, rec. (S.20°E., 39.24') 2004
No new accessories needed.
Corner maintenance/other info - clear brush from around monument and to BTs. Tie flagging to monument and guard posts, paint BT faces & a 6" band at head height, add new nails to existing BT tags & add new tags where needed.
Geodetic coordinates -
LAT: N42°48'37.55299" LONG: W122°51'50.20728"
Elipsoid height - 2360.8 ft
Datum - PER OPUS: NAD 83(2011)(EPOCH:2010.0000)
Source - RTK&STATIC GPS observations from OPUS corrected base.