

TOWNSHIP 32 RANGE 01 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Cor. Secs. 17, 18, 19, & 20

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Rufus S. Moore, Deputy Surveyor, under contract 475 dated July 3, 1883 - (DCSO records Vol. 19 Page(s) 8276)  
-----

A point about 200 ft. above branch and Set a dogwood post, 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 17, 18, 19, & 20, marked T32S S 17 on NE, R1W S 20 on SE, S 19 on SW, and S 18 on NW faces, with 3 notches on S & 5 notches on E edges; from which

- A fir, 36" dia. bears N.55°E., 31 lks mkd: T32S R1W S17 BT
- A fir, 10" dia. bears S.18°E., 47 lks mkd: T32S R1W S20 BT
- A fir, 12" dia. bears S.28°W., 16 lks mkd: T32S R1W S19 BT
- A fir, 30" dia. bears N.75°W., 9 lks. mkd: T32S R1W S18 BT

BLM Dependent resurvey by Hans W Thielsen, under Group #318, surveyed Aug/Sept 1955 - (DCSO records Vol. 28 Page(s) 12134)  
-----

The cor. of secs. 17, 18, 19, & 20, determined at record bearing & distance from the orig. BTs:

- A rotted fir stump, bears N.55°E., 31 lks., with no remaining marks.
- A fir, 14" dia., S.18°E., 47 lks., marked with a healed blaze.
- A fir snag, 12" dia., bears S.28°W., 16 lks., marks S R1W S19 uncovered.
- A fir, 30" dia., bears N.75°W., 9 lks., marked T32S R1W S18 BT.

At the corner point

Set an iron post, 36" long, 2" dia., 30" in the ground, with brass cap marked:

T32S	R1W
<u>S 18</u>	<u>S 17</u>
S 19	S 20
1955	

from which new BTs

- A fir, 18" dia. bears N.14°E., 30 lks mkd: T32S R1W S17 BT
- A fir, 28" dia., bears S.63½°E., 89 lks., mkd: T32S R1W S20 BT.
- A fir, 15" dia., bears S.54¼°W., 35 lks., mkd: T32S R1W S19 BT.
- A fir, 18" dia. bears N.5°W., 56 lks. mkd: T32S R1W S18 BT

Douglas Co. Surveyors Office - John M. Powell - 8/1968 - C.S. File 54/71  
-----

Found OK

Used this cor. for line to 19|20.

Put location tag 50.0 east of cor. on old skid Rd.

continued next page

TOWNSHIP 32 RANGE 01 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Cor. Secs. 17, 18, 19, & 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Glenn Baughman - For: USFS - Dec. 1976 - M56-69

-----  
Found - GLO BC properly marked.  
26" Fir bears N.19°E., 20.0 ft  
28" Fir bears S.85°E., 44.4 ft  
32" Fir bears S.60°E., 60.0 ft  
12" Fir bears S.22°W., 11.2 ft (snag)  
22" Fir bears S.51°W., 22.7 ft  
20" Fir bears N.3°W., 37.3 ft

Fd. Ok 12/1980 - B. Shaner, M79-68

BLM dependent resurvey by Francis J. Simon, Cadastral Surveyor under Group #2007, surveyed April/June 2002 - (DCSO records Vol. 54 Page(s) 21250-1)

-----  
The cor. of secs. 17, 18, 19, & 20, monumented with an iron post, 2" dia., firmly set, projecting 10" above the ground, with brass cap (properly) mkd.

from which remains of the original bearing trees

A broken off fir snag, size indeterminate, bears S.28°W., 10.6 ft., with scribe marks W S19 visible on detached blaze.

A fir, 31" dia., bears N.75°W., 7.7 ft., with scribe marks T3 S W visible on bark. (Record, 5.9 ft.)

and bearing trees mkd. by Thielsen

A fir, 30" dia., bears N.14°E., 20.6 ft., with a healed blaze. (Record, 19.8 ft.)

A fir, 32" dia., bears S.63½°E., 57.5 ft., with a healed blaze. (Record, 58.7 ft.)

A fir, 26" dia., bears S.54¼°W., 23.1 ft., with a healed blaze.

A fir, 29" dia., bears N.5°W., 37.0 ft., with a healed blaze.

and a BT reported by Baughman in 1976

A fir, 31" dia., bears S.88°E., 43.2 ft., with a bulldozer blade scar facing the cor.

Jackson Co. Surveyors Office - Kerry K Bradshaw, Jackson Co. Surveyor - B. Beeman & K. Durkee - March 29, 2010 (down loaded from internet 12/9/2010) - C.S. file 67/31-15

-----  
Found at the corner position, exposed 12", with steel posts 2 ft. west and 3 ft. east, the 2" diam. galv. iron pipe with a 2½" dia. brass cap set by the BLM in 1955 (properly) mkd: Original BTs recorded by Moore, in 1883 found and measured to center at base;

continued next page

TOWNSHIP 32 RANGE 01 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Cor. Secs. 17, 18, 19, & 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Fir rotted stob with exposed face scribed 'S19' brs.  
S.25°W., 11.1 ft. record; S.28°W, 10.6 ft to face  
D.Fir now 32" dia. with a healed blaze, brs. N.75°W., 7.3  
ft. record; 5.9 ft. to face  
Bearing trees recorded by the BLM in 1955 found with healed  
single blazes and measured to center at base;  
D.Fir now 34" dia. brs. record N.14°E., 19.8 ft.  
D.Fir sawed stump brs. record S.63½°E., 58.7 ft.  
D.Fir now 28" dia. brs. record S.54¼W., 23.1 ft.  
D.Fir now 32" dia. brs. record N.5°W., 37.0 ft.  
Marked a new BT "CS""BT" & measured to center at lower blaze  
Yew 9" dia. brs. S.62°E., 9.7 ft.  
Corner lies approx. 700 ft. southerly along blocked spur road  
then approx 100 ft. west.  
V. -18°25'