

TOWNSHIP 32 RANGE 01 POINT IDENTIFIER # 200440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 17 & 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Rufus S. Moore, Deputy Surveyor, under contract 475 dated July 3, 1883 - (DCSO records Vol. 19 Page(s) 8279)

A point about 250 ft. above sec. cor. and Set a basalt stone 16x10x6", 11" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which
 A fir, 8" dia., bears N.83°E., 17 lks., mkd: ¼ S BT.
 A fir, 4" dia., bears N.52°W., 33 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell - 7/19/1968 - C.S. File 54/71

Reported as not found.
(Rec. 8" & 4" Fir) Area heavily logged. Fd. mound of stone & stake at approx. cor.

Bruce Shaner - For: USFS - Dec. 1980 - M79-68

Set - Brass cap mkd: "T32S R1W WM ¼ S18 S17 RLS 430 1980"
BTs - 10" D.Fir, I scribed "¼ S18 BT" bears S.77°W., 17.9 ft.
 8" D.Fir, I scribed "¼ S17 BT" bears S.24°E., 26.0 ft.

Raymond Wytcherly - For: Boise Cascade Corp. - May 2004 - M144-50

Found - 1980 brass cap per M 79-68 from which
 D.Fir 18" dia., bears (S.24°E., 26.0 ft) face healed over.
 D.Fir 21" dia., bears (S.77°W., 17.9 ft) face healed over.
New BTs- Cedar 8" dia., bears N.74°E., 25.1 ft., scribed "¼ S 17 BT"
 Cedar 6" dia., bears N.21°W., 8.7 ft., scribed "¼ S 18 BT"
 Maple 7" dia., bears N.74°W., 18.7 ft., scribed "¼ S 18 BT"