

TOWNSHIP 32 RANGE 01 POINT IDENTIFIER # 200540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7 & 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Rufus S. Moore, Deputy Surveyor, under contract 475 dated July 3, 1883 - (DCSO records Vol. 19 Page(s) 8282)

A point about 300 ft. below sec. cor. and Set a maple post, 3 ft. long, 3" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S on W face; from which

- A fir, 35" dia., bears N.11°E., 31 lks., mkd: ¼ S BT.
- A fir, 10" dia., bears S.35°W., 8 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell - 7/24/1968 - C.S. File 54/71

Reported as not found.
Found N-S blazed line. East side of line old logging & burnt.

Bruce Shaner - For: USFS - Dec. 1980 - M79-67

Set - Brass cap mkd. T325 R1W WM ¼ S7 S8 RLS 430 1980
From which a:
34" W.Fir, orig. BT. scribes visible bears S.35°W., 5.3 ft.
40" D.Fir stump, orig BT bark scribes "BT visible bears N.64°E., 20.5 ft. to face (Rec. N.11°E.)
New - 26" Cedar BT, I scribed "¼ S8 BT" bears N.2°E., 22.1 ft
10" Cedar BT, I scribed "¼ S7 BT" bears S.63°W. 14.6 ft