

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Rufus S. Moore, Deputy Surveyor, under contract 475 dated July 3, 1883 - (DCSO records Vol. 19 Page(s) 8285)

Set a basalt stone 12x10x8", 8" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which
 A fir, 8" dia., bears N.20°E., 6 lks., mkd: ¼ S BT.
 A matherone, 14" dia., bears S.40°E., 8 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - July 1968 - C.S. File 54/71

Found - 12x10x8" stone mkd: "¼" on W face.
 8" now 13" D.Fir N.20°E., 4.0 ft. shows good scar.
 14" Laurel, now hole, S.40°E., 5.3 ft.
Set brass cap at cor. mkd: COUNTY SURVEYORS T32S R1W
 OFFICE 1968 ¼ S 6 | S 5
New BT - 8" Yew S.63°W., 14.8 ft. mkd: ¼ S6 CS BT.
This corner lies on NW slope approx. 280.0 ft south of creek.

Bruce Shaner, RLS #430 - For: USFS, Tiller Ranger Dist. - Oct. 1980 - RM 3-37

Found - 1968 County brass cap.
 12"x10"x8" orig. stone "¼" lies alongside Brass cap.
 16" D.Fir, orig. BT, blown down, healed face bears N.20°E., 4.0 ft. to root hole
 8" Yew, BT, scribes visible bears S.63°W., 14.8 ft.
New BT - 20" D. Fir BT, I scribed "¼ S5 BT" bears N.72°E., 35.4 ft.

Fd. Ok by R. Wytcherley May 2004 - M144-50