

TOWNSHIP 32 RANGE 01 POINT IDENTIFIER # 300640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 4 & 5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Rufus S. Moore, Deputy Surveyor, under contract 475 dated July 3, 1883 - (DCSO records Vol. 19 Page(s) 8273)

Set a basalt stone 16x12x6", 11" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which

A fir, 22" dia., bears N.68°W., 27 lks., mkd: ¼ S BT.

A fir, 20" dia., bears S.56°E., 24 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - July/Aug. 1968 - C.S. File 54/71

Found - Stone at corner, approx. size, but no marks.
22", now 24" D.Fir, N.68°W. 17.8 ft., shows good scar.

20", now 22" D.Fir, S.56°E. 15.8 ft., prev. opened, scribe visible.

Set brass Cap at Cor. mkd: COUNTY SURVEYORS T32S R1W
Office, 1968 ¼ S 5 | S 4

Note - All Bearing Trees OK and Tagged.