

TOWNSHIP 32 RANGE 01 POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 9 & 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Rufus S. Moore, Deputy Surveyor, under contract 475 dated July 3, 1883 - (DCSO records Vol. 19 Page(s) 8264)

A point about 100 ft. above last creek and Set a basalt stone 14x10x6", 10" in the ground for 1/4 sec. cor. mkd. 1/4 on W face, from which

- A yew, 14" dia., bears N.75°E., 20 lks., mkd: 1/4 S BT.
- A fir, 8" dia., bears S.43°W., 18 lks., mkd: 1/4 S BT.

BLM Dependent resurvey by Hans W Thielsen, under Group #318, surveyed Aug/Sept 1955 - (DCSO records Vol. 28 Pages 12136-7)

The 1/4 sec. cor. of secs. 9 & 10 determined at the record bearing & distance from each of the orig. BTs, as follows:

- A yew, 18" dia., bears N.75°E., 20 lks., with marks 1/4 S BT, uncovered.
- A fir, 14" dia., bears S.43°W., 18 lks., with marks 1/4 S BT, uncovered.

At the corner point

Set an iron post, 36" long, 1" dia., 30" in the ground, with brass cap marked:

1/4
S 9 | S 10
1955

from which new BTs

- A yew, 8" dia., bears S.47°E., 41 lks., mkd: 1/4 S10 BT.
- A fir, 8" dia., bears S.35 1/2°W., 30 lks., mkd: 1/4 S BT.

Fd. Ok by DCSO, JMP - 7/1968 - C.S. 54/71