TOWNSHIP 32 RANGE 01 POINT IDENTIFIER # 440400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Rufus S. Moore, Deputy Surveyor, under contract 475 dated July 3, 1883 - (DCSO records Vol. 19 Pages 8261-2)

Set a basalt stone 18x10x6", 12" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which

A fir, 14" dia., bears N.80°E., 16 lks., mkd: ¼ S BT.
A fir, 4" dia., bears S.55°W., 5 lks., mkd: ¼ S BT.

BLM Dependent resurvey by Hans W Thielsen, under Group #318, surveyed Aug/Sept 1955 - (DCSO records Vol. 28 Pages 12132-3)

Point for the ¼ sec. cor. of secs. 15 & 22, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 36 long, 1" dia., 24" in the ground to solid rock, and in a mound of stone to top, with brass cap marked:

¼ S 15 / S 22
1955

from which

A R.Fir, 50" dia., bears N.55½°E., 186 lks., mkd: ¼ S15 BT
A W.Fir, 20" dia., bears S.39¼°E., 31 lks., mkd: ¼ S22 BT.

Kurt C. Weaver, LS1679 - Witnesses: Herb Farber & Reg Harding - Nov. 1978 - C.S. File 58/176

Found - A 1" pipe with brass cap attached set by H.W. Thielsen, 1955
A W.Fir 24" bears rec. S.39¼°E., 20.5 ft.

I perpetuate the corner position by taking the following new tree and place a brass washer bearing my registration No. in the lower blaze:

A D.Fir 8" marked ¼ S BT bears N.41°E., 70.1 ft.