

PRIMARY CORNER DESCRIPTION Cor. Secs. 14, 15, 22, & 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Rufus S. Moore, Deputy Surveyor, under contract 475 dated July 3, 1883 - (DCSO records Vol. 19 Pages 8253-4)

Set a basalt stone 12x10x6", 8" in the ground for cor. of secs. 14, 15, 22, & 23 400 ft. above sec. cor. mkd with 3 notches on S & 2 notches on E edge, from which

- A fir, 12" dia. bears N.58°E., 3 lks. mkd: T32S R1W S14 BT
- A fir, 14" dia. bears S.72°E., 10 lks mkd: T32S R1W S23 BT
- A fir, 12" dia. bears S.28°W., 30 lks mkd: T32S R1W S22 BT
- A fir, 13" dia. bears N.47°W., 31 lks mkd: T32S R1W S15 BT

BLM Dependent resurvey by Hans W Thielsen, under Group #318, surveyed Aug/Sept 1955 - (DCSO records Vol. 28 Page(s) 12130)

The cor. of secs, 14, 15, 22 & 23, determined at record bearing & dist. from the remains of the original SE & NW BTs:

- A fir stump, 28" dia., bears S.72°E., 10 lks., marked with the lower part of a blaze.
- A fir stump, 14" dia., bears N.47°W., 31 lks., marked with the lower part of a blaze. The sawed off tree lies downhill, 108 lks. mkd T32S R1W S15 BT.

At the corner point

Set an iron post, 3 ft. long, 2" dia., 30", in the ground, with brass cap marked

T32S	R1W
<u>S 15</u>	<u>S 14</u>
S 22	S 23
1955	

from which new BTs

- A fir, 15" dia. bears N.48°E. 89 lks. mkd: T32S R1W S14 BT
 - A fir, 23" dia., bears S.83½°E., 51 lks., mkd: T32S R1W S23 BT.
 - A fir, 30" dia., bears S.62¼°W., 137 lks., mkd: T32S R1W S22 BT.
 - A fir, 30" dia. bears N.35°W., 90 lks mkd: T32S R1W S15 BT
- Latitude: 42°46¾'N Longitude: 122°47½'W.

Marvin Ramsey - For: Robert D. Chamberlain - Oct. 1958 (Filed Dec. 29, 1992) - C.S. File 63/147 A-F

The locus of the cor. of secs. 14, 15, 22, & 23 is determined at the record bearings & distances, form the BTs by Hans W Thielsen. The iron post set by Thielsen does not show & has the appearance of having been removed by a logging operation.

At the corner point

Set an iron pipe, 3 ft. long, 2" dia., 18" in the ground with mound of stone to top, mkd: RS404; from which

continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 14, 15, 22, & 23

Alias	Description
Alias	Description
Alias	Description
Alias	Description

N.48°E., 89 lks., to a stump; A D.Fir 15" dia., has been up-rotted by a logging operation & is close by on the ground, mkd. T32S R1W S14 BT.
 A D.Fir 24" dia., bears S.83½°E., 51 lks. mkd: T32S R1W S23 BT.
 A D.Fir 30" dia., bears S.62¼°W., 137 lks. mkd: T32S R1W S22 BT.
 A D.Fir 30" dia., N.35°W., 90 lks., mkd: T32S R1W S15 BT. and New BT
 A D.Fir 6" dia., N.20°E., 212 lks., mkd: T32S R1W S15 RS404 BT
 The geographic position of this corner is latitude 42°46'50"N and longitude 122°47'48"W. The observed magnetic declination is 21°45'E.

Kurt C Weaver, LS #1679 - Witnesses: Herb Farber & Reg Harding - Nov. 1978 - C.S. File 58/176-6

 Found - 2" O.D. pipe by Marvin Ramsey in 1958, firmly set in mound of stone.
 D.Fir 30" with healed blaze, bears S.62¼°E., 92.5 ft. (Rec. S.62¼°W., 90.4 ft.)
 D.Fir 30" dia. w/open blaze bears N.35½°W., 57.8 ft. (record N. 35°W. 59.4 ft.)
 A dead-standing D.Fir 24" dia. bears S.84°E., 33.0 ft. (record S. 83½°E. 33.7 ft.)
 BT by Ramsey
 A dead-standing D.Fir 9" dia., bears N.22¼°E., 137.6 ft. (rec. N.20°E., 139.9 ft.)
 I set a 2" dia., x 30" G.I.P. over the found pipe with a 2½" brass cap mkd:
 T32S R1W
 S 15|S 14
 S 22|S 23
 LS 1679 1978
 and take the following new BTs & place a brass washer bearing my registration No. in the lower blaze.
 A D.Fir 6" dia. marked "T32S R1W S14 BT" bears N.70¼°E. 26.5 ft.
 A D.Fir 6" dia. mkd "T32S R1W S23 BT" bears S.1°E. 25.1 ft.

Gerald Nygren, LS 1035 - For: USFS - July 1989 - C.S. 63/85

 Found - 1½" iron pipe with 3" brass cap extended 4" above stone mound. 1978
 30" D.Fir S.62¼°W., 92.5 ft. (healed blaze)
 continued next page

TOWNSHIP 32 RANGE 01 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Cor. Secs. 14, 15, 22, & 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

24" Fir snag S.84°E., 33.0 ft. (vis. scribe)
32" D.Fir, N.35½°W., 57.8 ft. (vis. scribe)
8" D.Fir N.70¼°E., 26.5 ft. (healed blaze)
12" D.Fir S.1°E., 25.1 ft. (healed blaze)
New BT - A 8" D.Fir S.84°E. , 22.6 ft. scribed "T32S R1W S23
BT" with ½" dia. brass washer mkd. "LS 1035"
nailed to lower blaze.