

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 2 & 3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Rufus S. Moore, Deputy Surveyor, under contract 475 dated July 3, 1883 - (DCSO records Vol. 19 Page(s) 8259)

Set a basalt stone 16x8x8", 11" in the ground for 1/4 sec. cor. mkd. 1/4 on W face, from which

A fir, 7" dia., bears N.70°W., 23 lks., mkd: 1/4 S BT.

A fir, 4" dia., bears S.28°E., 21 lks., mkd: 1/4 S BT.

Art Boyer - Witnesses: Herb North craft & Ted Shattenkirk - Sept. 1949 - C.S. file 40/214

Searched for three days for this cor. which is supposed to be on a hill sloping to the E which is covered with loose rocks and trash, decayed limbs and small trees. There are so many loose rocks around that the orig. rock could not be located and the BTs which were 4" & 7" fir tree could not be found. Set this corner by proportional measurement bet. the SE & NE corner of this sec. Raised a mound of rocks, basalt, about 18" high and placed a 3"x3" fir post for corner, from which

18" Fir bears N.78°W., 28 ft. scribed 1/4 S3 BT 1581.

12" Fir bears S.37°E., 17.3 ft. scribed 1/4 S2 BT 1581.

There are many old growth fir trees with a 600 ft. radius of this corner or where it would come if it were 1/2 mi. N of the SE corner of this sec. so it might seem that the cor. was never set.

This new cor. as set is 18 ft. W of the center of a creek and N.37°E., approx. 100 ft. from a rock ledge which is about 10 ft. high and 50 ft. long N & S

Gerald V. Nygren, LS 1035 - For: Umpqua Nat'l Forest - Aug. 1980 - M79-53 & C.S. 58/158N

No evidence found of corner set by A. Boyer in 1949.

Set - 2 1/2"x30" alum. pipe with alum. cap mkd: "T32S R1W WM 1/4 3*2 1980 PLS 1035" exposed 6" above ground set at prorated position.

BTs - 6" D.Fir bears N.79°E., 15.8 ft.

8" D.Fir bears S.51°W., 29.2 ft.

BTs have brass washer stamped "RS 1035 nailed to lower blaze.

Gerald V. Nygren, PLS #1035 - For: USDA, Umpqua Nat'l Forest - July 1991 thru Sept. 1993 - M 118-20 - C.S. File 63/134 (N)

Set -2 1/2" x 30" alum pipe with alum cap stamped: T32S R1W WM
1/4 S3|S2

Reset 1993

1980

PLS 1035

continued next page

TOWNSHIP 32 RANGE 01 POINT IDENTIFIER # 500640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 2 & 3

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

New - Hemlock, 8" dia. bears S.16°E., 3.4', scribed "¼ S2 BT"
Hemlock, 10" dia. bears N.26°E., 3.3' scribed "¼ S2 BT"
D.Fir, 10" dia., bears N.36°W., 11.2' scribed "¼ S3 BT"
Hemlock, 17" dia. bears S.30°W. 16.5' scribed "¼ S3 BT"
A 5/8" x 30" iron rod with yellow plastic cap mkd:
"NYGREN LS 1035", bears N.0°32'44"W., 275.07'.
(Previous location of ¼ cor. per 1980 survey)