

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 14

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Rufus S. Moore, Deputy Surveyor, under contract 475 dated July 3, 1883 - (DCSO records Vol. 19 Pages 8256)

-----  
Set fir post, 3 ft. long, 3" sq., 24" in the ground, for 1/4 sec. cor., marked 1/4 S on N side; from which  
A fir, 20" dia., bears N.45°W., 7 lks., mkd: 1/4 S BT.  
A fir, 14" dia., bears S.5°W., 20 lks., mkd: 1/4 S BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - July/Aug. 1968 - C.S. File 54/71

-----  
Found - Orig. 20", now 30" D.Fir N.45°w., 4.6 ft., shows good scars.  
Orig. 14" D.Fir, now stob, S.5°W. 16.1 ft (Rec 13.1) open for scribe "1/4S"  
Set brass cap at cor. mkd: COUNTY SURVEYORS T32S R1W  
OFFICE 1/4 S 11  
1968 S 14  
New BT - 15" D.Fir S.59°W., 18.3 ft. mkd: "1/4 S14 CS BT"

Gerald Nygren - For: USFS - July 1989 - C.S. File 63/85

-----  
Found - 1968 County 1" iron pipe with 2 1/2" brass cap extended 9" above ground. 1968  
29" dia. D.Fir N.50°W., 4.7 ft. (healed blaze) (N.45°W., 4.6)  
11 dia. D.Fir S.4°19'E., 16.6 ft. (vis. scribe) (S.5°W., 16.6)  
18" dia. D.Fir snag S.58°54'W., 17.4 ft. (S.59°W. 18.3 ft.)  
New BT - 7" dia. D.Fir, S.59°E., 35.1 ft. scribed "1/4 S14 BT". Nailed 1/2" brass washer marked "LS 1035" to lower blaze.

Leonard Herzstein - USFS -9/9/2003 - Witness: Brandon Green - C.S. File 65/48-25A&B

-----  
Found - 1 1/4" outside dia. iron pipe, loosely set, projecting 10" above the ground with a 2 1/2" dia. brass cap, per Powell.  
From which the OBTs  
12" dia. D.Fir snag, bears S.5°W., 16.1 ft (rec. 13.2 ft), with scribe marks "S 1/4 BT" visible on previously opened blaze)  
32" dia. D.Fir snag, bears N.45°W., 4.6 ft, with a healed double blaze & a third healed blaze by Powell in 1968. continued next page

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 14

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

and BT marked by Powell in 1968:

20" dia. D.Fir snag, bears S.59°W., 17.9 ft. (rec. 18.3 ft) with partially healed double blaze.

and BT marked by Nygren in 1989;

7" dia., W.Fir, bears S.59°E., 34.0 ft. (rec. D.Fir, 35.1 ft.) with healed double blaze.

New - From which new accessories for the corner:

6" diam. W.Fir, bears N.42¼°W., 18.6 ft, scribed "¼ Sll BT" on a single blaze.

A steel fence post, bears N.82¼°W., 2.4 ft, projecting 4 ft above the ground with Forest Service signs "Boundary" (#54-2) & "Attention" (#54-4) attached

Note - Bearing & distances were determined by a total station traverse from a property line post 575 ft West of the corner. I used a bearing of S.89°53'34"E. between the property line post & the corner, based on a 1978 property line survey. At the corner point, I determined the magnetic declination to be 15°E. Bearings are reported to the nearest ¼°. Trees are measured to the center of the root crown. Tree diameters are at breast height. A ¾" brass washer, marked "LS 2150", is nailed flush to the lower portion of the blaze of the new bearing tree.

The corner is East, 305 ft, from Forest Service Road No. 1632 (at mile post 8.3) & West, approx. 250 ft, from the Rogue-Umpqua Divide