

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 2 & 11

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Rufus S. Moore, Deputy Surveyor, under contract 475 dated July 3, 1883 - (DCSO records Vol. 19 Pages 8257-8)

Set a basalt stone 16x12x6", 11" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
 A fir, 8" dia., bears N.52°W., 16 lks., mkd: ¼ S BT.
 A fir, 14" dia., bears S.20°W., 5 lks., mkd: ¼ S BT.

Gerald V. Nygren, LS 1035 - For: Umpqua Nat'l Forest - Aug. 1980 - M79-53 & C.S. 58/158N

No evidence of this corner fd as set by Rufus Moore in 1883. Set - 2½"x30" alum. pipe with alum. cap mkd: T32S R1W WM S2, S11 1980 PLS 1035" exposed 8" above ground set by proportionate measurement.
 10" Hemlock bears S.70°W., 26.5 ft.
 6" Hemlock bears N.39°W., 12.8 ft.
BTs have brass washer stamped "RS 1035" nailed to lower blaze

Ed McGinty, Jackson Co. Surveyor - R. Frost, R. Templin - Witness: T. Newcomb, USFS - May 7, 1981 - C.S. file 58/138-16

Found - Orig. Fir, now rotted fir stump remains by R. Moore in 1883) with portions alongside containing old axe work & scribed (partial) "BT" bears record S.20°W., 3.30 ft. to estimated orig. position of scribed face.
 Orig. rotted fir root & stump remains, containing old axe work, fd at record location of orig NW BT
 The orig. stone is now gone.
 A fd. 2" dia., alum. pipe, projecting 5" with alum. cap mkd: T32S R1W WM ¼ 2 1 1980 PLS 1035 (1989) set by proportionate method, on survey No. 8498 (Jackson Co) & M79-53 (Douglas Co.) bears S.86°24'E., 48.75 ft.

Set - From the above orig. evidence at the location described, SET a 2x32" galv. IP 28" in the ground, for the corner with a 2½" dia., brass cap mkd: T32S R1W ¼S 2 11 CS 1981
 Mound stones around corner, mk new trees "CS" "BT" and take measurement to center of trees at lower blaze.
New BTs- D.Fir 9" dia. bears S.27°54'W., 17.00 ft. (5.18 m)
 Hemlock, 13" dia., bears N.63°50'W., 21.10 (6.43 m)
Corner lies on steep (90%) North slope an estimated 400 ft. North of road along top of Umpqua Divide ridge top.

continued next page

TOWNSHIP 32 RANGE 01 POINT IDENTIFIER # 540600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 2 & 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Gerald V. Nygren, PLS #1035 - For: United States Department of Agriculture, Umpqua National Forest - July 1991 thru Sept. 1993 - M 118-20 - C.S. File 63/134 (N)

Found - 2"x32" galvanized iron pipe with a 2½" dia., brass cap (properly) stamped:
D.Fir, 11" dia., bears S.28°W., 17.0' visible scribe
Hemlock, 15" dia. bears N.64°W. 21.1' visible scribe
New - Hemlock, 11" dia., bears S.77°W. 18.4', scribed "¼ S11 BT"
D.Fir, 9" dia. bears N.80°E. 23.2' scribed "¼ S2 BT"
5/8"x30" iron rod with yellow plastic cap mkd:
"NYGREN LS 1035", bears S.86°26'27"E., 48.75'.
(Previous location of ¼ cor.) (1981)